

110/127 V - 220/240 V level gauge light fitting for non-armoured cable increased safety



0965 32 level gauge light fitting 1 x 36W

Installation in
vertical position



18, 36 and 58 W level gauge light fitting





- Ø 26 mm tube, standard G13 caps
- Frequency : 50/60 Hz
- Power supply via high frequency ballast according to model:
110/127 V ± 10% AC/DC or 220/240 V ~ ± 10%, 198 to 264 V
- Instant start. Power factor ≥ 0.95
- Pre-impregnated fibre glass reinforced polyester body
- Polycarbonate diffuser hinged to body
- Lighting concentrated on level indicator
- High temperature internal wiring
- Elastomer gasket
- Anti-vibration lampholders with spring system
- Power supply to the unit cut off by positive safety switch which operates when diffuser is opened, for replacing tube with mains power switched on
- Open and close using an Allen key or flat screwdriver (system automatically protects against over turning)
- IP 2X terminal strip cover for maintaining the ballast and lampholders without cutting off the main power supply
- Ballast fixed by screws, equipped with a fast connector

Level gauge light version

- Three threaded cable entries, 2 at one end and the third at the opposite end for M25 cable gland.
- Supplied with :
 - One M25 polyamide cable gland (sealed Ø 8 to 18.5 mm)
 - Two M25 blanking plugs
 - One 5 x 4 mm² max. flexible or 5 x 6 mm² max. rigid connection terminal block

Tube (W) not supplied	Weight (kg)	Volume (dm ³)	Cat. No. 110/127 V	Cat. No. 220/240 V	Pack
1 x 18	5.5	32.3	0915 31	0965 31	1
1 x 36	7.9	54.2	0915 32	0965 32	1
1 x 58	9	65	0915 33	0965 33	1

Fixing accessories

	Cat. No.	Pack
Set of 2 half clamps for fixing to Ø 49 mm (1" 1/2) or Ø 42 mm (1" 1/4) tube	0965 93	1
For fixing to Ø 60 mm (2") tube	 0965 91	1
Set of 2 aluminium brackets for fixing unit to flat surface	0965 97	1
316 stainless steel version	 0965 90	1
Set of 2 aluminium hinged brackets for adjusting direction of luminaire when wall-mounted.	0965 98	1
316 stainless steel version	 0965 74	1
Set of 2 zinc-plated steel brackets for quick fixing with one hand	0965 96	1
316 stainless steel version	 0965 89	1

For special options, please consult us:

- Ø 38 mm standard or bi-pin tubes specially designed for low temperatures
- Special protection of the diffuser against severe chemical attack

Dimensions of fixing accessories (see page 36-37)

Installation and connection method (see page 38-39)

Spare parts (see page 290)

Timer switch (see page 211)