

## Luminaires

In a separate, comprehensive catalog, Appleton also offers a complete line of products for hazardous locations, fully tested to NEC and CEC standards. Ask your local representative about the Appleton brand or visit the Appleton web site at [www.appletonelec.com](http://www.appletonelec.com) for details.



### Compliances

- Class I, Div. 2, Groups A,B,C,D
- Class II, Div. 2 Groups E,G
- Marine Type Electric Fixture Outside Type (Salt Water)
- NEMA 4X

### Materials

- Housing: Fiberglass reinforced polyester
- Lens: Polycarbonate
- Hubs: Stainless steel

### Features

- No tools required to access lamps
- Integral switch disconnects power to ballast and lamps when lens is opened

### Wattage Range

- (2) or (4) 40W F40BX PL Fluorescent
- (2) 32W T8 Linear Fluorescent
- (2) 44W T8-HO Linear Fluorescent
- (2) 40W T12 Linear Fluorescent
- (2) 60W T12-HO Linear Fluorescent
- (3) 32W T8 Linear Fluorescent

### Input Voltage and Frequency

- 120V, 60Hz
- 277V, 60Hz
- Others upon request

Refer to Appleton Master Catalog Section F3 for more information

## Luminaires



### Compliances

- UL Listed
- CSA Certified
- Class I, Div. 2, Groups A,B,C,D
- Class II, Div. 1 and 2; Groups E,F,G
- Class III
- NEMA 4X
- CSA 4X
- Simultaneous Exposure  
Class I, Div. 2; Class II, Div. 1

### Materials

- Housing: Copper free aluminum with epoxy powder coating
- Globe: Heat resistant glass
- Hardware: Stainless steel

### Features

- Multiple optical choices

- Cool operating temperature
- Superior corrosion resistance

### Wattage Range

- 35W–400W High Pressure Sodium
- 50W–400W Mercury Vapor
- 50W–400W Metal Halide
- 150W–400W Pulse Start Metal Halide

### Input Voltage and Frequency

- 120V, 60Hz
- 208V, 60Hz
- 240V, 60Hz
- 277V, 60Hz
- 480V, 60Hz
- Others upon request

Refer to Appleton Master Catalog Section F1 for more information



### Areamaster Series

### Compliances

- General Duty
- Marine Duty
- Class I, Div. 2 Groups A,B,C,D Hazardous Location

### Materials

- Housing : Copper free aluminum with bronze polyester coating
- Lens : Tempered glass
- Gaskets: Silicone rubber

### Features

- Slip fit or trurnium mounting available
- Corrosion resistant

### Wattage Range

- 70W–1000W High Pressure Sodium
- 175W–1500W Metal Haloid
- 100W–1000W Mercury Vapor
- 200W–400W Pulse Start Metal Halide

### Input Voltage and Frequency

- 120V, 60Hz
- 208V, 60Hz
- 240V, 60Hz
- 277V, 60Hz
- 480V, 60Hz
- Others upon request

Refer to Appleton Master Catalog Section Q for more information