

Cylindrical fluorescent luminaires 220/230 V - 60 Hz for armoured and non-armoured cable **flameproof**



0948 11 FLD 2 x 58W



0948 10 FLD 2 x 36W



0948 09 FLD 2 x 18W

0948 09 with reflector 948 69
and protective guard 0948 73

18, 36 and 58 W cylindrical fluorescent luminaires with ferromagnetic ballast

- Ferromagnetic ballast
- Ø 26 or 38 mm twin tubes, G13 lampholders
- Borosilicate glass sealed tube
- Zamak end caps and cover anticorrosion treated and painted grey
- Threaded access cover with O ring seal
- High temperature internal wiring
- Connection via 2 x 3 x 2.5 mm² terminals
- Two M20 threaded cable entries
- Supplied with an M20 blanking plug (cable gland not supplied)
- External earth via bracket : 4 mm²
- Operates in any position
- Fixed using 2 integrated lugs (see accessories opposite)

For Ø 26 or 38 mm G13 fluorescent tubes

- Compensated power supply 220 V +6% - 10% , 60 Hz (power factor ≥ 0.90). Starter ignition

Tube (W) (not supplied)	Group	Weight (Kg)	Volume (dm ³)	Cat. No. 220 V - 60 Hz	Pack
2 x 18	IIC	9.7	58	0948 09	1
2 x 36	IIB	15.3	99	0948 10	1
2 x 58	IIB	18.2	119	0948 11	1

- Compensated power supply 230 V +6% - 10% , 60 Hz (power factor ≥ 0.9). Starter ignition

Tube (W) (not supplied)	Group	Weight (Kg)	Volume (dm ³)	Cat. No. 230 V - 60 Hz	Pack
2 x 18	IIC	9.7	58	0948 18	1
2 x 36	IIB	15.3	99	0948 19	1
2 x 58	IIB	18.2	119	0948 20	1

Accessories

Reflectors

White painted galvanized steel,
guard fitted separately

	Cat. No.	Pack
0948 09/18	0948 69	1
0948 10/19	0948 70	1
0948 11/20	0948 71	1



Protective guards

Zinc-plated steel (20 microns),
reflector fitted separately

	Cat. No.	Pack
0948 09/18	0948 73	1
0948 10/19	0948 74	1
0948 11/20	0948 75	1



Fixings - set of 2 brackets

	Cat. No.	Pack
Quick fixing, zinc-plated steel	0948 97	1
316 stainless steel version	0948 89	1
Fixing on flat surface, zinc-plated steel	0948 98	1
316 stainless steel version	0948 90	1
With zinc-plated brackets for fixing on		
- 1" 1/4 (Ø 42 mm) or 1" 1/2 (Ø 49 mm) tube	0948 99	1
- 316 stainless steel version	0948 92	1
- 2" (Ø 60 mm) tube	0948 91	1
- 316 stainless steel version	0948 93	1
Fall prevention fixing kit (1.20 m stainless steel chain)	0938 19	1



For special options, please consult us:

- **254 V + 6% - 10%**
- **Version with three Ø 26 tubes**
- **Tubes designed for cold applications, for increasing the flux at low temperature**
- **Hinged fixing with chain**
- **Three entry version**

Spare parts (see page 290)

Cable gland for armoured cable (see page 252-262)

