

Cylindrical fluorescent luminaires 110/127 V - 220/240 V - 50/60 Hz for armoured and non-armoured cable **flameproof**



0948 13 FLD 2 x 58W



0948 08 FLD 2 x 36W



0948 07 FLD 2 x 18W



0948 07 with reflector 0948 69 and protective guard 0948 73

18, 36 and 58 W fluorescent luminaires with high frequency electronic ballast

- Ø 26 or 38 mm tubes, G13 lampholders
- Borosilicate glass sealed tube
- Zamak end caps and cover anticorrosion treated and painted grey
- Threaded access cover with O ring seal
- Connection via 2 x 3 x 2.5 mm² terminals
- High temperature internal wiring
- Two M20 threaded cable entries
- Supplied with an M20 blanking plug (cable gland not supplied)
- External earth via bracket : 4 mm²
- Operates in any position
- Fixed using 2 integrated lugs

Instant start Ø 26 or 38 mm G13 tubes

- Power supply 110/127 V, ± 10% - 50/60 Hz, 110/127 V DC
- Electronic ballast (power factor ≥ 0.95)

| Tubes (W) (not supplied) | Group | Weight (Kg) | Volume (dm ³) | Cat. No. 110/127 V | Pack |
|-----------------------------|-------|----------------|------------------------------|-----------------------|------|
| 2 x 18 | IIC | 9.7 | 58 | 0918 07 | 1 |
| 2 x 36 | IIB | 15.3 | 99 | 0918 08 | 1 |
| 1 x 58 | IIB | 17 | 119 | 0918 12 | 1 |
| 2 x 58 | IIB | 18.2 | 119 | 0918 13 | 1 |

- Instant start 220/240 V, ±10% - 50/60 Hz
- Electronic ballast (power factor ≥ 0.95)

| Tubes (W) (not supplied) | Group | Weight (Kg) | Volume (dm ³) | Cat. No. 220/240 V | Pack |
|-----------------------------|-------|----------------|------------------------------|-----------------------|------|
| 2 x 18 | IIC | 9.7 | 58 | 0948 07 | 1 |
| 2 x 36 | IIB | 14.9 | 99 | 0948 08 | 1 |
| 1 x 58 | IIB | 17 | 119 | 0948 12 | 1 |
| 2 x 58 | IIB | 18.2 | 119 | 0948 13 | 1 |

Accessories

Reflectors

White painted galvanized steel, guard fitted separately

| | Cat. No. | Pack |
|---------------------|----------------|------|
| 0948 07 and 0918 07 | 0948 69 | 1 |
| 0948 08 and 0918 08 | 0948 70 | 1 |
| 0948 13 and 0918 13 | 0948 71 | 1 |
| 0948 12 and 0918 12 | | |

Protective guards

Zinc-plated steel (20 microns), reflector fitted separately

| | Cat. No. | Pack |
|---------------------|----------------|------|
| 0948 07 and 0918 07 | 0948 73 | 1 |
| 0948 08 and 0918 08 | 0948 74 | 1 |
| 0948 13 and 0918 13 | 0948 75 | 1 |
| 0948 12 and 0918 12 | | |

Fixings - set of 2 brackets

Quick one-hand fixing, zinc-plated steel

| | Cat. No. | Pack |
|---|----------------|------|
| 316 stainless steel version | 0948 97 | 1 |
| Fixing on flat surface, zinc-plated steel | 0948 89 | 1 |
| 316 stainless steel version | 0948 98 | 1 |
| With zinc-plated brackets for fixing on | | |
| - 1" 1/2 (Ø 49 mm) or 1" 1/4 (Ø 42 mm) tube | 0948 99 | 1 |
| - 316 stainless steel version | 0948 92 | 1 |
| - 2" (Ø 60 mm) tube | 0948 91 | 1 |
| - 316 stainless steel version | 0948 93 | 1 |
| Fall prevention fixing kit (1.20 m stainless steel chain) | 0938 19 | 1 |

For special options, please consult us:

- Version with three Ø 26 tubes
- Tubes designed for cold applications, for increasing the out put at low temperature
- Hinged fixing with chain
- 3/4 NPT cable entries
- Three entries version

Spare parts (see page 290)

Cable gland for armoured cable (see page 252-262)

