


0951 57 + 0951 94



Quick access to the lamp

## 150 to 1000 W floodlights

- Compensated power supply 230/240 V ( $\pm 10\%$ ) 50 Hz  
– Power factor  $\geq 0.9$  (except 0951 61)
- Grey painted marine grade aluminium alloy body
- Toughened glass sealed onto body
- Highly polished anodised aluminium internal reflector
- Increased safety terminal box
- E40 lampholder
- Adjustable lampholder to change lighting from narrow to wide angle
- Rapid access to the lamp via threaded cover with safety chain
- Direct access to the components via screw-on cover: ballasts, igniters, capacitors separated from the lamp housing, ensuring total thermal insulation
- Operates in any position subject to lamp performance  
– 2 self-tightening connection terminals: capacity  $2 \times 6 \text{ mm}^2$  maximum  
– 2 earthing terminals capacity  $6 \text{ mm}^2$  - External earth  $4 \text{ mm}^2$

Two M20 through wiring cable entries: supplied with

- One M20 cable gland (sealed  $\varnothing 6.5$  to  $14.5 \text{ mm}$ ) - non armoured
- One M20 blanking plug and two M20 locknuts

### Catalogue numbers

Permissible lamps (not supplied)	Type		Weight (Kg)	Volume (dm <sup>3</sup> )	Cat. No. 230/240 V	Pack.
	(1)	(2)				
150 W HP sodium	x	x	27	104.4	<b>0951 55</b>	1
250 W HP sodium	x	x	28	104.4	<b>0951 56</b>	1
400 W HP sodium		x	30	104.4	<b>0951 57</b>	1
600 W HP sodium		x	33	104.4	<b>0951 60</b>	1
250 W mercury vapour	x	x	28	104.4	<b>0951 62</b>	1
400 W mercury vapour		x	28.5	104.4	<b>0951 58</b>	1
250 W metal halide	x	x	28	104.4	<b>0951 63</b>	1
400 W metal halide		x	30	104.4	<b>0951 59</b>	1
500 W / 1000 W halogen		x	25	104.4	<b>0951 61</b>	1
(1) Ovoid - (2) Tubular						

## Accessories

	Cat. No.	Pack
Galvanised steel hinged brackets	0951 94	1
Set of 2 galvanised steel clamp brackets for:		
- Fixing on 1" 1/4 ( $\varnothing 42 \text{ mm}$ ) or 1" 1/2 ( $\varnothing 49$ ) tube	0951 98	1
- Fixing on 2" ( $\varnothing 60$ ) tube	0951 90	1
Guard to be fixed by screws (1)	0951 85	1
Screw-on overhead diffuser (1) (galvanised steel, black painting)	0951 86	1
Screw-on protective guard (1) (zinc plated steel)	0951 87	1
Set of horizontal fixings (galvanised steel)	0951 88	1
Fixation sur tube 1' 1/4 ( $\varnothing 42 \text{ mm}$ ) ou 1' 1/2 ( $\varnothing 49 \text{ mm}$ ) (galvanised steel)	0951 71	1
Fixation sur tube 2" (60 mm) (galvanised steel)	0951 89	1
400 W mercury vapour cylindrical lamp	0948 95	1

(1) These 2 accessories cannot be fitted together

### For special options, please consult us:

- 110/127 V 50/60 Hz - 208 V - 254 V, 50 Hz
- 2 additional terminals for 3-phase + neutral 380/415 V  
(loopin loopout connection possible)
- Temperature class T4

Spare parts (see page 290)

Cable gland for armoured cable (see page 252-262)

