

IIB/IIC portable floodlights and handlamps - 12/24 V AC/DC 110/230 V - 50/60 Hz flameproof



0951 50
Portable
floodlight 70W



0947 97
Fluorescent
handlamp 8W



0947 92
incandescent
handlamp

Portable wide beam floodlight

For halogen lamps

- Grey painted marine grade aluminium body and bezel
- Sealed toughened lamp glass
- Threaded flameproof joint
- Plastic covered carrying handle
- One M20 threaded rear cable entry
- Lamp H3 NORMA, OSRAM (PK 22S lampholder) 55 W 12 V - 70 W 24 V
- Operates in any position
- Installed on cradle to allow for all adjustments on site and in any location
- Connection via 2 x 2 x 2.5mm² terminals - Internal earth : 1 x 2.5 mm²
- External earth : 4 mm²

Permissible lamps (supplied)	Supply voltage	Weight (Kg)	Volume (dm ³)	Cat. No.	Pack
Halogen 55 W	12 V AC/DC	8	27	0951 49	1
Halogen 70 W	24 V AC/DC	8	27	0951 50	1
Halogen 70 W	230 V - 50/60 Hz (1)	8	27	0951 53	1
Halogen 70 W	110 V - 50/60 Hz (2)	8	27	0951 52	1

(1) With transformer 230/24 V (+6% -10%)

(2) With transformer 110/24 V (+6% -10%)

Portable handlamps

For 8 W fluorescent lamp

- Power supply : 24 V (18 to 30 V) 50/60 Hz.
- 1 cable entry via integrated cable gland fitted with a 8 to 12 mm ring
- Power : approx. 400 mA
- Aluminium reflector clipped to the inside of the zinc-plated steel guard
- Toughened glass tube
- Neoprene handle and suspension hook
- Threaded flameproof joint
- Aluminium end caps, handle and cable entry unit
- Connection via 3 x 2.5 mm² terminals

Permissible lamp (supplied)	Weight (Kg)	Volume (dm ³)	Cat. No.	Pack
Fluorescent 8 W - 24 V - G5 cap	2.1	6	0947 97	1

For 75 W max. class III incandescent bulb

SELV

- Power supply : 24 V
- Grey painted aluminium alloy body and bezel
- Sealed borosilicate lamp glass
- E27 lampholder
- One M20 threaded cable entry
- White zinc-plated steel protective guard
- Threaded flameproof joint
- Connection to lampholder via 2 x 1 x 2.5 mm² terminals
- Fitted with suspension hook

Permissible lamp (not supplied)	Weight (Kg)	Volume (dm ³)	Cat. No.	Pack
Incandescent 75 W class III-SELV	2.8	13	0947 92	1

For special options, please consult us