



0951 17 + 095084
Static beacon + globe



0951 21
Flashing beacon



0950 84
Red globe

Beacons for marking and signalling

- Colourless sealed shock resistant lamp glass
- Grey marine grade aluminium alloy body and bezel
- Threaded flameproof joint. Closed by screwing on the bezel
- High temperature internal wiring
- Connection in increased safety "e" compartment via two 2 x 6 mm² self-tightening terminals or 6 mm² terminals (lug not supplied) + 1 earth terminal per cable entry (4 mm²)
- External earth 4 mm². Operates in any position
- 2 laterals entries threaded M20
- Supplied with :
 - 1 x M20 cable gland (sealed \varnothing 6.5 to 14.5 mm not armoured)
 - 1 x M20 blanking plug

Static beacon for 100 W max. incandescent lamp

- E27 lampholder. Lamp not supplied.
- Supplied without external coloured globe (see accessories)

	Weight	Volume	Cat. No.	Pack
100 W max.	7.5	30	0951 17	1

Rotating beacon for 40 W incandescent lamp

- Rotation speed : approximately 170 rpm
- E14 lampholder. Lamp supplied.
- Supplied without external coloured globe (see accessories)

Supply voltage	Amp valve	Weight (Kg)	Volume (dm ³)	Cat. No.	Pack
48 V \pm 10% - 50/60 Hz	1 A	8.5	30	0951 22	1
48 V DC \pm 10%	1 A	8.5	30	0951 23	1
110 V \pm 10% - 50/60 Hz	0.5 A	8.5	30	0951 24	1
230/240 V \pm 10% - 50/60 Hz	0.23 A	8.5	30	0951 25	1

5 joule flashing beacon

- Red flash tube (supplied)
- Instantaneous power : 50000 cd
- Flash rate : 1 per second
- Service life of tube : 70% luminosity after 8 million flashes
- Operating factor : 100%

Supply voltage	Tolerance	Power	Weight	Volume (Kg)	Cat. No. (dm ³)	Pack
230 V ~ 50/60 Hz	185 V - 255V	55 mA	8.5	30	0951 21	1
110 V ~ 50/60 Hz	90 V - 135V	110 mA	8.5	30	0951 14	1
48 V ~ 50/60 Hz	40 V - 54V	180 mA	8.5	30	0951 15	1
24 V ~ 50/60 Hz	20 V - 30V	220 mA	8.5	30	0951 16	1
110 V =	88 V - 132V	90 mA	8.5	30	0951 18	1
48 V =	40 V - 60V	150 mA	8.5	30	0951 19	1
24 V =	18 V - 35V	230 mA	8.5	30	0951 20	1

Accessories

Coloured polymethacrylate globe (external fixing)

	Cat. No.	Pack
- red	0950 84	1
- green	0950 85	1
- orange	0950 89	1
- transparent	0950 90	1
Protective guard (version without globe only)	0947 73	1
Wall bracket	0950 79	1



M 10 eye bolt

0950 81 1




Plate for installation on ceiling

0950 82 1

For special options, please consult us :

- Other colours
- Spare parts (see page 290)
- Cable glands for armoured cable (see pages 252-262)

NEW

