



Flashing beacon 0949 74
+ fixing unit 0948 98



Illuminated indicator bank
0949 89 + fixing unit 0948 89

Illuminated signalling

- Borosilicate glass sealed tube
- Zamak end cap and cover, anticorrosion treated and painted grey
- Threaded access cover with O ring seal
- Connection to plug-in terminal block via 2 x 3 2.5 mm² terminals
- External earth via bracket: 4 mm²
- Fixed using 2 integrated lugs with brackets
- Operates in any position
- Two M20 threaded cable entries
- Supplied with an M20 blanking plug (cable gland not supplied)

15 joule flashing beacon

- Red flash tube supplied
 - Instantaneous power : 150 000 cd
 - Flash rate : 45 per minute
- Operating factor: 10 min stop after 1 hour's operation
 - Service life of tube : 70% luminosity after 8 million flashes

| Supply voltage | Amp valve | Weight (Kg) | Volume (dm ³) | Cat. No. | Pack |
|---------------------------------|-----------|-------------|---------------------------|----------------|------|
| 24 V DC (18 - 30 V) | 700 mA | 6.8 | 31 | 0949 71 | 1 |
| 48 V DC (40 - 60 V) | 350 mA | 6.8 | 31 | 0949 72 | 1 |
| 110 V 50/60 Hz (95 - 127 V) | 270 mA | 6.8 | 31 | 0949 73 | 1 |
| 230 V 50/60 Hz (185 - 255 V) | 190 mA | 6.8 | 36 | 0949 74 | 1 |




3-stage illuminated indicator bank

- Indicator bank consisting of 3 interchangeable coloured modules (green, yellow and red) with the possibility of coupling 2 modules together for simultaneous lighting
- Static beacons
- For lamps 5/7 W max. with BA15d lamphoder
- Lamps not supplied (choose lamps suitable for the supply voltage)
- Connection to plug-in connector via 2 x 5 2.5 mm² terminals


| Permissible lamps for power supply | Lamp holder | Weight (Kg) | Volume (dm ³) | Cat. No. | Pack |
|------------------------------------|-------------|-------------|---------------------------|----------------|------|
| 5/7 W max. | BA15d | 6.8 | 36 | 0949 89 | 1 |

Accessories

Fixings-set of 2 brackets

| | | Cat. No. | Pack |
|--|---|----------------|------|
| Quick one-hand fixing, zinc-plated steel |  | 0948 97 | 1 |
| 316 stainless steel version | | 0948 89 | 1 |
| fixing unit on flat surface, zinc-plated steel |  | 0948 98 | 1 |
| 316 stainless steel version | | 0948 90 | 1 |
| With zinc-plated brackets for fixing | | | |
| - on 1" 1/2 (Ø 49 mm) or 1" 1/4 (Ø 42 mm) tube | | 0948 99 | 1 |
| 316 stainless steel version | | 0948 92 | 1 |
| - on 2" (Ø 60 mm) tube |  | 0948 91 | 1 |
| 316 stainless steel version | | 0948 93 | 1 |

Protective guards

| | | | |
|---|---|----------------|---|
| Zinc-plated steel (20 microns) |  | 0948 72 | 1 |
| Fall prevention fixing kit (1.20 m stainless steel chain) | | 0938 19 | 1 |

• Illuminated indicator bank with different number of stages, different combinations

- white and blue
- flashing
- flash discharge
- LED lighting

- Other voltages
- Spare parts (see page 290)
- 5 joule flashing beacon (see page 114)

Cable glands (see pages 252-263)