



500073

Flexible unions

Male/Male

- Must be used with fire-retardant unions or unions for pipes (see page 267)

Tapered thread (NPT)	Length (mm)	Weight (Kg)	Volume (dm ³)	Cat. No.	Pack
1/2"	100	0.65	1	500060	1
1/2"	170	0.7	1,75	500061	1
1/2"	250	0.7	2,5	500106	1
1/2"	300	0.75	3	500062	1
1/2"	400	0.8	4	500063	1
1/2"	500	0.85	5	500064	1
1/2"	600	0.9	6	500065	1
1/2"	700	0.95	7	500066	1
1/2"	800	1	8	500067	1
1/2"	900	1.05	9	500068	1
1/2"	1000	1.1	10	500069	1
3/4"	300	0.75	3	500070	1
3/4"	400	0.8	1	500071	1
3/4"	500	0.85	5	500072	1
3/4"	600	0.9	6	500073	1
3/4"	700	0.95	7	500074	1
3/4"	800	1	8	500075	1
3/4"	900	1.05	9	500076	1
3/4"	1000	1.1	10	500077	1
1"	300	0.75	3	500078	1
1"	400	0.8	1	500079	1
1"	500	0.85	5	500080	1
1"	600	0.9	6	500081	1
1"	700	0.95	7	500082	1
1"	800	1	8	500083	1
1"	900	1.05	9	500084	1
1"	1000	1.1	3	500085	1
1"1/4	300	0.75	3	500086	1
1"1/4	400	0.8	3	500087	1
1"1/4	500	0.85	5	500088	1
1"1/4	600	0.9	6	500089	1
1"1/4	700	0.95	7	500090	1
1"1/4	800	1	8	500091	1
1"1/4	900	1.05	9	500092	1
1"1/4	1000	1.1	10	500093	1
1"1/2	300	0.75	3	500094	1
1"1/2	400	0.8	1	500095	1
1"1/2	500	0.85	5	500096	1
1"1/2	600	0.9	6	500097	1
1"1/2	700	0.95	7	500098	1

Part number in bold : fast moving references

Zone 1 et 2

ATEX

II 2 G

EEx d IIC

TECHNICAL DATA

Zones :

- 1 and 2

Classification:

- According to CENELEC
- Conforming to the ATEX directive
- Conforming to standards EN 50014-18
- 0722 II 2 G, EEx d IIC for gas

Certification :

- Approved type SPH
- CENELEC CESI 00 ATEX 048 U
- Declaration of conformity 5C226 for components

Operating temperature :

- 20°C to + 40°C